
Digital Pressure Meter

PM205

- *Range: from -1 to 1000 bar, selectable bar/psi*
- *Accuracy < 0.1 % FS*
- *1000 hours continuous operation, auto power off*
- *High reliability, high resistance against shocks*
- *Protection class: IP65*
- *Well suited for marine and industrial applications*
- *Type approved by DNV-GL for use onboard ships*



DNV·GL

The **PM205** - digital pressure meter is a microprocessor controlled, accurate and versatile digital pressure measuring and calibration instrument with integrated fast peak-, max.- and min.- function.

The instrument is used in two modes:

MANO-Mode: The pressure is measured twice per second and displayed. The top display indicates the actual pressure, the bottom display shows the MAX.- or MIN.- pressure since the last RESET.

PEAK-Mode: The pressure is measured 5,000 times per second and is brought to the display twice per second.

The **PM205** has a ZERO function that allows the user to set any value as a new zero reference. Barometric pressure variations can thus be compensated. The digital pressure meter is supplied with an internal battery with 1000 hours continuous operation in MANO-Mode, guaranteed by the AUTO SWITCHOFF function, which activates if no key inputs are detected within the previous 15 minutes.

This digital pressure gauge finds its specific utilization in marine industry, onboard ships and mobile offshore units and in general manifold industrial fields.

The **PM205**, supplied with all relevant certificates, will serve as a valuable first line pressure calibration and measurement instrument.

Technical information

Range	Resolution	Overpressure
-1 to 3 bar	1mbar	10 bar
-1 to 30 bar	10 mbar	60 bar
0 to 60 bar	10 mbar	120 bar
0 to 300 bar	100 mbar	400 bar
0 to 700 bar	200 mbar	700 bar
0 to 1000 bar	200 mbar	1000 bar
Accuracy RT (room temperature)	< 0,1 %FS	
Total Error Band (0 to 50 °C)	< 0,2 % FS	
Storage-/ Operating Temperature	-20 to 70 °C / 0 to 50 °C	
Compensated Temperature Range	0 to 50 °C	
Power supply	3.0V type CR2430	
Auto power off	15 min.	
Battery life	1000 hours continous operation MANO-Mode 150 hours of continous operation in PEAK-Mode	
Standard process coupling	¼" BSP MALE, Swivel	
Dimensions	118mm (h) x 42mm (d), ø76mm (w)	
Weight	0,21 kg	
Display	LCD	
Selectable read out	bar, mbar/hPa, kPa, MPa, PSI, kp/cm2	
Peak function	Max. or Min.	
Zero function	Yes	
Readings per second	5000 (PEAK mode)	
Protection class (CEI 529)	IP65	

Intrinsically safe version, 94/9/CE

Classification:  II 1 G EEx ia IIC T6 or T5

Certification File: LCIE 01 ATEX 6001 X

The EEx ia version of PM205 incorporates an additional protection switch.

Functions, ranges and accuracy are identical to the standard version.

IKM Instrutek AS is a leading supplier for calibration of instruments for vessels. We offer a maintenance scheme for our customers calibration kit, including a pool of re-certified test cases, ready to be shipped to vessels.

We manage the system for our customers and ensure that traceable and certified instruments are available anytime. The Marine Test Case, Mini System, covers E0 requirements from SOLAS

We offer custom designed cases including a wide range of instruments including certificates and approvals for: Pressure, Temperature, Electrical and Gas

IKM Instrutek AS provide test cases, calibration- and service world-wide through a network of distributors and service partners.

IKM Instrutek AS

Elveveien 28

3262 Larvik, Norway

T: +47 33 16 57 00

F: +47 33 16 57 01

E: marineservice.ikminstrutek@IKM.no

Distributed by:

www.IKM.com

