





- ① PLASTIC VALVE BOX TO PROVIDE ACCESS.
- ② 3M DBR/Y-6 SPLICE KIT OR EQUIVALENT DIRECT BURIAL SPLICE KIT
- ③ DIRECT BURIAL 1 PAIR, TWISTED SHIELDED CABLE. RECOMMENDED MINIMUM CONDUCTOR SIZE 18 AWG. RATED FOR DISTANCES UP TO 2,000 FT (610 M). ENSURE A SERVICE LOOP (EXTRA WIRE LENGTH) IS PROVIDED AT THE FLOW SENSOR IN CASE MAINTENANCE IS NEEDED
- ④ QS200 ULTRASONIC FLOW SENSOR
- ⑤ TEE COMPATIBLE WITH QS200 (FLOMEC QS200 TEE RECOMMENDED FOR BEST RESULTS). SELECT TEE SIZE PER APPLICATION FLOW RATES REQ'D (SEE DATA SHEET)
- ⑥ QUICK RELEASE PIN
- ⑦ GRAVEL - GRAVEL SHALL BE PLACED AT BOTTOM OF QS200 TEE AND SHALL BE A MINIMUM OF 10-INCH THICK (10-INCH DEEP)

NOTE 1:
5Xs MEANS 5 TIMES PIPE'S INNER DIAMETER AND 10Xs MEANS 10 TIMES PIPE'S INNER DIAMETER

NOTE 2:
FOR 1-INCH THRU 4-INCH PIPE INSTALLATIONS, THIS ANGLE IS ESPECIALLY IMPORTANT AND SHOULD BE SET AT 60-90 DEGREES FOR MOST ACCURATE QS200 OPERATION

NOTE 3:
BURIED CABLE ENROUTE TO IRRIGATION CONTROLLER



01 SECTION A-A
N.T.S.

00 FLOMEC FLOW SENSOR INSTALLATION
N.T.S.

IND-1125 REV D

QS200 FLOW SENSOR INSTALLATION



Great Plains Industries, Inc. / 888-996-3837 / FLOMEC.net
Great Plains Industries, Inc. Australia / +61 2 9540 4433 / FLOMEC.net