

DUOIQ

Dual-Gas Monitor with Advanced Modular Sensor Technology

An award-winning dual-gas detector with extended battery life, modular sensors, and seamless connectivity for enhanced safety.



reddot winner 2026



DuoIQ is a compact, dual-gas monitor designed to provide workers with versatile, reliable protection against multiple hazards. Built with a long-lasting rechargeable battery life and every major sensor technology, DuoIQ provides safety in environments where detecting two gases is critical but equipment size and cost need to be optimised.

FEATURES & BENEFITS

Dual-gas detection

The only dual-gas detector with the capability to detect a wide range of gas combinations, providing flexibility for diverse applications without the need for bulky, multi-gas devices.

Extended battery life

DuoIQ boasts one of the longest battery lives of any dual-gas monitor, reducing recharge frequency and operational downtime. It offers up to one-month of use based on standard 8-hour shifts*. Between-shift charging keeps devices operational, with full recharge achieved in under 3 hours.

Pre-calibrated sensor trays

DuoIQ's sensor trays are easy to swap, eliminating the need to send the device back to the manufacturer for maintenance. Additionally, the plug-and-play modular design provides flexibility to target different gases.

Comprehensive sensor technology

DuoIQ features unique sensor combinations, made possible by its wide variety of sensor technologies, including electrochemical, infrared (IR), pellistor, and long-life oxygen (O₂) sensors.

Optimised for safety & compliance

DuoIQ integrates seamlessly with Crowcon Connect for real-time monitoring, compliance tracking, and asset management, improving safety and ensuring regulatory requirements are met. Effortlessly store and retrieve calibration certificates in Crowcon Connect to simplify audits.

Lightweight, compact design

With its compact design, DuoIQ delivers reliable performance in a lightweight form - measuring just over 10cm in height and weighing only 139.8g**, ensuring portability and ease of use.

Bluetooth® & NFC connectivity

With Bluetooth® and Near Field Communication (NFC) connectivity, DuoIQ can push data to Crowcon Connect via IQhub. This enables live data streaming, remote configuration, and detailed insights for enhanced safety and device performance.

One button for multiple functions

Single-button operation simplifies the user experience with quick, intuitive control, reducing complexity and learning curves, while making the device more widely accessible.



SPECIFICATIONS

DEVICE SPECIFICATIONS		GASES & RANGES		
SIZE	Standard: 96 x 55 x 32 mm Deep tray: 106 x 55 x 32 mm	GAS	RANGE	RESOLUTION
WEIGHT**	139.8g (Weight may vary depending on configuration)	Ammonia	0-100ppm	0.1ppm
DURABILITY	6m drop test	Butane	0-100% LEL	1% LEL
RESPONSE TIME (T90)	<10s (sensor dependent)	Carbon Dioxide	0-2% volume	0.01% volume
ALARMS	Visual, vibrating, audible (95dB), low/high, TWA, STEL	Carbon Monoxide	0-250ppm	1ppm
DISPLAY	Backlit segment display	Chlorine	0-10ppm	0.1ppm
DATA LOGGING	Up to 500 event logs	Hydrogen Sulfide	0-100ppm	0.1ppm
POWER & BATTERY*	Tox / O2 tox : 7 days, (20 days at 8 hour shifts) Tox / O2 IR: 1 day (4 days at 8 hour shifts) Tox / O2 Pellistor: 1 day (3 days at 8 hour shifts) Recharge time: 0-80% 2 hours 0-100% <3 hours	Methane	0-100% LEL	1% LEL
SAMPLING	None	Nitrogen Dioxide	0-20ppm	0.1ppm
OPERATING TEMPERATURE RANGE	-20 to +55°C / -4 to +131°F	Oxygen	0-25% volume	0.1% volume
HUMIDITY	0-95% RH	Ozone	0-1ppm	0.1ppm
INGRESS PROTECTION	IP66 & IP68	Sulphur Dioxide	0-20ppm	0.1ppm
APPROVALS	CSA US: Class I, Division 1, Groups A, B, C, D T4* ATEX: Ex II 1G Ex ia IIC T4 Ga IECEX: Ex ia da IIC T4 Ga INMETRO: Ex ia IIC T4 Ga* RED/FCC/IC: Wireless *Pending			
CALIBRATION & MAINTENANCE	Automatic bump tests (<10 seconds) and calibrations (<30 seconds) through IQhub; Manual bump and calibrations through device and PC software			
ACCESSORIES	Power cable (device to USB-A & USB-C); Flow plate; IQhub			
CONNECTIVITY	NFC & Bluetooth® (optional) required for connection to Crowcon Connect App			
CROWCON CONNECT	Cloud-hosted web application for safety monitoring and asset management, offering real-time alarms, compliance dashboards, location tracking, device configurations, and essential reporting			
SENSORS	Electrochemical, IR, Pellistor and Long life O ₂			
LANGUAGES	English			
WARRANTY	2 years (sensor warranty separate)			

Disclaimer

Due to ongoing research and product improvement, specifications are subject to change without notice. While every effort has been made to ensure accuracy in this document, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This document is not intended to form the basis of a contract.

For more information:

t: +44 (0)1235 557700
e: info@crowcon.com
w: www.crowcon.com

Locate your Regional Sales Representative at:
www.crowcon.com/contact-us/where-to-buy

© 2026 Crowcon Detection Instruments Ltd.